

Computable Functions, the Church-Turing Thesis and the Quantum Measurement Problem

R. Srikanth*

Optics Group, Raman Research Institute Bangalore- 560 080, Karnataka, India.

It is possible in principle to construct quantum mechanical observables and unitary operators which, if implemented in physical systems as measurements and dynamical evolution, would contradict the Church-Turing thesis, which lies at the foundation of computer science. Elsewhere we have argued that the quantum measurement problem implies a finite, computational model of the measurement and evolution of quantum states. If correct, this approach helps to identify the key feature that can reconcile quantum mechanics with the Church-Turing thesis: finitude of the degree of fine-graining of Hilbert space. This suggests that the Church-Turing thesis constrains the physical universe and thereby it highlights a surprising connection between purely logical and algorithmic considerations on the one hand and physical reality on the other.

PACS numbers: 02.10.Ab, 03.65.Ta

Quantum mechanical measurements on a physical system are represented by observables- Hermitian operators on the state space of the observed system. It is an important question whether all observables and all unitary evolutions may be realized, in principle on physical systems [1]. It turns out that ideas from computer science are crucial to the analysis. The reason is that some problems that are classically considered uncomputable can sometimes be recast as appropriate quantum observables or unitary operations, which, if physically implementable, could apparently render them computable. There has appeared to be no known principle that forbids the implementation of such quantum mechanical observables or unitary dynamics. If feasible, they would imply that quantum mechanics not only impacts computational complexity, in terms of speeding up certain computations [2], but also impacts *computability*. In a remarkable work that founded modern computer science, Turing [3, 4] defined a class of functions now known as recursive or computable functions. The *Church-Turing thesis* [5] of computer science states that these functions correspond precisely to any *effective* or *mechanical* method for obtaining the values of a mathematical function. The Church-Turing thesis is fundamental to theoretical computer science, since it asserts that the mathematical class of functions studied by computer scientists, the computable functions, is the most general class of functions that may be effectively calculated by any physical means. It is an empirical statement, not a mathematical theorem, that has been verified over 65 years of testing [4, 6].

The present work reexamines the question of whether, accepting the Church-Turing thesis as an informal guiding principle for physics [7], we can identify a principle that can reconcile this conflict between it and the general model of computation that quantum mechanics seems to make possible. Naturally, for specific systems particular measurements and unitary dynamics could be precluded by some system specific features, such as superselection rules. We will not be concerned with such specific features, but rather with general considerations. In fact, we find that we cannot be confined to the physical realm of measurement and dynamics, but are led to examine the algorithmic foundations of physical processes, in the light of the computational model of quantum measurement [8].

For convenience, we refer to computable partial functions of a single non-negative integer as *programs*. The qualification ‘partial’ signifies that there may be some input values for which the function is not defined. An example of a program is the function $f(x) = x^3$, which may be computed using a suitable mechanical procedure (a Turing machine). On the other hand, an example of a function that does not stop or *halt* for some input, and is thus undefined for that input, is $f(x) \equiv$ “the smallest number that is the sum of x squares”, which will not halt on $x = 4$ [9].

The question of whether or not a given program, numbered p (according to any consistent enumeration scheme, such as Gödel numbering) halts on input i is obviously a question of considerable practical importance: we would like to know whether a given algorithm will terminate or not. To understand this better, Turing defined the *halting function* $h(p, i)$ as some algorithm to decide whether program p halts on input i and demonstrated using a *reductio ad absurdum* argument that the halting problem is not a decidable. A version of this argument is as follows. Suppose we define the halting function by:

$$h(p, i) = \begin{cases} 0 & \text{if } p(i) \text{ loops endlessly,} \\ 1 & \text{otherwise,} \end{cases} \quad (1)$$

and diagonal function $r(n)$ by:

$$r(n) = \begin{cases} 0 & \text{if } h(n, n) = 0, \\ \text{loops endlessly} & \text{otherwise.} \end{cases} \quad (2)$$

Suppose $r(n)$ is computable and this can be ascertained by running $h(r, n)$. Yet, setting $n = r$ above, we find $r(r) = 0 \Leftrightarrow h(r, r) = 0 \Leftrightarrow r(r)$ diverges, which is a clear contradiction. Thus, $r(n)$ cannot be computable. Since the computability of $h(p, i)$ would imply that of $r(n)$, it follows that the halting function is also noncomputable here. This is related to Gödel's incompleteness theorem that says that if a consistent axiomatic system is rich enough to be self-referential, then it will be incomplete in that true but unprovable statements can be made in it [10].

It is reasonable to expect that quantum computation does not impact computability, since the latter appears to follow mostly from logical considerations rather than any model of computation [11]. Moreover, one might expect that noncomputability might be embedded right in the (classical) specification of the implementation of such otherwise hypercomputational operations. A quantum algorithm can in principle side-step this contradiction, by distinguishing quantum and classical algorithms. A *quantum* function $qh(p, i)$, similar to Eq. (1), can conceivably exist to determine whether the classical program will halt on input i or not. The above contradiction would be avoided if $qh(p, i)$ cannot take as argument the modified program $r(n)$, which is now of *quantum* character because it calls $qh(p, i)$ as subroutine [12]. This follows from the fact that $qh(p, i)$ can accept only integers (enumerations of programs, such as Gödel numbering), while quantum programs have to be labelled by real numbers, which have a larger cardinality than integers. The idea is that the computer should not be powerful enough to compute its own diagonal function, which if it is, leads to the above contradiction. However, this suggests that a quantum algorithm can in principle compute the halting problem for Turing machines.

Let us consider Hilbert's tenth problem, the Entscheidungsproblem (decision problem), which asks for a procedure to decide whether a given Diophantine equation (polynomial with integer coefficients) $D(x)$ has a solution in the domain of natural numbers, i.e., $x \equiv (x_1, \dots, x_n) \in \mathbb{N}^n$. This is known to be Turing uncomputable [13]. However, suppose we define a 'Diophantine evolution', U_D , by:

$$U_D \equiv \sum_{x=0}^{\infty} |D^2(x), x\rangle \langle x|, \quad (3)$$

where $\{|x\rangle\}$ is an orthonormal basis for the state space of some physical system with a countably infinite dimensional state space. Here $|D^2(x), x\rangle$ is a state with energy eigenvalue $D^2(x) \equiv (D(x))^2$. It is easy to verify that U_D is unitary. We note that U_D is equivalent to measuring a 'Diophantine observable' $\hat{D}$:

$$\hat{D} \equiv \sum_{x=0}^{\infty} D^2(x) |x\rangle \langle x|, \quad (4)$$

If one can design a Hamiltonian that effects U_D , then the *search* for a solution to $D(x)$ is equivalent to *checking* whether the ground state of the Hamiltonian has energy $E_g = 0$. An exhaustive search can never terminate if no solution exists, which is a manifestation of the undecidability of the Entscheidungsproblem. However, in the quantum case, if the required Hamiltonian can be prepared, and its ground state accessed in finite time, then a *single* check suffices to decide whether $D(x)$ has a solution [12]. It is clear that the success of the above method depends on superposition in Fock space and the guarantee that the ground state minimizes energy. The power of the ground state oracle derives from "energy tagging", which appears to be more powerful than a usual quantum search oracle.

If we may abstract the computational model that this quantum procedure embodies, devoid of any physical content, and idealize it, the result is what may be called an *infinite Turing field* $\mathcal{T}(\aleph_0, \aleph_0)$: the set of countably infinite ($\aleph_0$) Turing machines T_x simultaneously evaluating $D(x)$, a total recursive function, on each possible value of x , having infinite memory, and the power to communicate instantaneously with each other (i.e, message passing rate = $\aleph_0/\text{sec}$), such that the moment some T_x finds $D(x) = 0$ on its x , all T_x 's are brought to halt, and, deterministically, precisely this value x and no other is printed out. The twin arguments of $\mathcal{T}(\aleph_0, \aleph_0)$ signify that it is composed of infinitely many Turing machines that are able to talk to each other infinitely fast. In modern computer terminology, this is akin to a computer having infinite RAM and infinite clockrate. Note that this is a well-defined model because the set of all possible values of n -tuples $x \in \mathbb{N}^n$ has the same cardinality ($\aleph_0$) as the set of natural numbers $\mathbb{N}$. An alternate definition of $\mathcal{T}(\aleph_0, \aleph_0)$ is that it is a Turing machine that performs calculations infinitely fast (i.e, at the rate of $\aleph_0$ logical operations per second, or ops). $\mathcal{T}(\aleph_0, \aleph_0)$ transcends the Turing barrier by performing infinite calculations in finite time. Further, by stipulating that it accepts only problems of finite size, we ensure that it is not powerful enough to compute its own diagonal function and thus remains logically consistent for our present needs. The proposed quantum algorithms for computing Turing uncomputable functions [12, 14] are in effect emulating a probabilistic version of $\mathcal{T}(\aleph_0, \aleph_0)$, where the level of confidence can be made arbitrarily high as time increases. They involve a countably infinite dimensional Hilbert space, where each dimension in the generic quantum superposition corresponds to a Turing machine in the field $\mathcal{T}(\aleph_0, \aleph_0)$.

A demonstration that a quantum computer, even probabilistically, emulates $\mathcal{T}(\aleph_0, \aleph_0)$ would violate the Church-Turing thesis, for it would demonstrate an effective algorithm to compute a function that is Turing uncomputable. There is an implicit and quite reasonable assumption on which the Turing barrier transcendence attributed to quantum algorithms rests: the presumed infinitude of the universe, in particular, of Hilbert space. However, the computational model for quantum measurement (CMQM) [8] suggests that, insofar as the quantum state dynamics of physical systems may be regarded as information registered and computations performed by the (quantum) universe, the latter is equivalent to a *finite* Turing field: a finite number of Turing machines interlinked by finite speed message passing. If true, then this furnishes a very basic algorithmic-physical principle why quantum computers cannot break through the Turing barrier. What is the evidence for this principle? In Ref. [8], we argue that *the quantum measurement problem* is the required evidence.

A simple recapitulation of the measurement problem is as follows. Suppose we have a spinor prepared in the state $|+\rangle_x = (1/\sqrt{2})(|+\rangle_z + |-\rangle_z)$ and a macroscopic meter that measures the observable $\hat{\sigma}_z$. The meter has three macroscopic states, given by $\{|+\rangle_M, |-\rangle_M, |0\rangle_M\}$. If the spinor exists in one of the $\hat{\sigma}_z$ eigenstates, the meter gives a measurement according to the interaction: $|\pm\rangle_z|0\rangle_M \rightarrow |\pm\rangle_z|\pm\rangle_M$. Yet, when the state $|+\rangle_x$ is measured, this does not lead to a superposition according to $|+\rangle_x|0\rangle_M \rightarrow (1/\sqrt{2})(|+\rangle_z|+\rangle_M + |-\rangle_z|-\rangle_M)$, as the principle of linearity suggests, but probabilistically to *one* of the outcomes $|\pm\rangle_z|\pm\rangle_M$. The absence of macroscopic superpositions, that one would naturally expect during measurement via system-apparatus entanglement, is the measurement problem.

In CMQM, the dynamical evolution of physical systems are modeled as computational acts on an abstract, finite, algorithmic structure underlying physical reality. The apparent break-down in linearity noted above and the mesoscopic threshold at which it presumably occurs are related to a finite degree of fine-graining of the Hilbert space of physical systems (in general, of the universe). The fine-graining parameter μ (in bits per amplitude; $\mu/2$ bits each specifying the real and the imaginary part) specifies the precision to which states, and their unitary evolution, can be specified in principle. According to the ‘principle of computational resolution’ enunciated in the model, μ should be large enough to support a uniform superposition. That is, in a system of n qubits, each amplitude in a uniform superposition $\sum_{j=0}^{2^n-1} \lambda_j |j\rangle$ is given by $|\lambda_j| = 2^{-n/2}$, which should be greater than $2^{-\mu/2}$, so that (roughly) $n \leq \mu$. If a system, through entanglement engendered by interaction with its environment, becomes larger than this, i.e., the dimension of its Hilbert space exceeds 2^μ , the system is said to become computationally unstable because the computational and mnemonic support for its physical evolution is overwhelmed, and to discontinuously suffers an information transition to a separable state chosen probabilistically. Such transitions in the abstract memory registers are identified with the ‘state vector reduction’ or ‘collapse of the wavefunction’. Subsequent interaction again drives the exponential enlargement of the system’s state space via entanglement with its environment. The continual cycle of alternating dynamical evolutions and information transitions is responsible for the appearance of classicality at the macro-level, which is described by the Lindblad equation [15]. Therefore, μ determines the Heisenberg cut, the mesoscopic threshold that presumably separates the quantum microcosm from the classical macrocosm. If no such cut existed, CMQM implies that macroscopic superpositions would be ubiquitous, which they aren’t (for comments on the important role of decoherence, cf. [8]). In short, in this light we infer that the classicality of the macroscopic world implies a finite computational and memory support of the universe for the evolution of physical systems, equivalent to a *finite Turing field* $\mathcal{T}(M, V)$, where $M, V < \aleph_0$.

In the case where the large dimension arises from accessible excited states, rather than from interactions, the finite value of μ implies an upper bound to number of basis states that can be evolved coherently in a superposition, given by about 2^μ , because amplitudes that are in principle magnitudinally much smaller than $2^{-\mu/2}$ will be re-set to zero, with concomitant loss of information from the state. If the number of ‘important’ superposed states is sufficiently small, which is the situation in most cases, this truncation effect is hardly significant. However, when the evolution passes through intermediary states where amplitude can be spread out among a large number of states, approaching the above bound, the deviation from unitary evolution can be significant. The apparent behaviour of the system will be one whose unitary evolution is interrupted because of decoherence or of having been measured. In a complicated energy landscape of states, the system can collapse into a local minimum. The evolution would no longer be given by an equation of the form Eq. (3), but of a more general positive operator that leads to a final state that is mixed.

We can use observations to bound M and V from above. If S represents the entropy of an isolated system, then CMQM implies (roughly) that the memory corresponding to it (ie., the total information required to specify its microstate in $\mathcal{H}_\mu$, the finitely fine-grained Hilbert space) is about $M \equiv e^{S/k_B} \mu$ and total speed of computation that corresponds to sustaining the evolution of the system is about $V = 2^{\mu/2} e^{S/k_B} E/\hbar$ ops, where E is energy of the system. Suppose for instance that the largest object whose unitary evolution (run at μ bit precision) can be stably supported by the universe is an Avogadro number of qubits, beyond which the system becomes computationally unstable and hence classical. Then μ can be estimated to be about 10^{23} bits, from which one can estimate $M \approx 2^{10^{23}} 10^{23} \approx 2^{10^{23}}$ bits and $V \approx 2^{1.5 \times 10^{23}} E/\hbar \approx 2^{1.5 \times 10^{23}}$ ops (for more realistic estimates, cf. Ref. [8]). Not surprisingly, the memory

overhead and the computational speed of all conventional computers combined is far lesser. With about 10^9 computers equipped with terabit memory and operating at a clock rate of about 10^9 Hz performing about 10^5 elementary logical operations per clock cycle, all the human-made computers in the world can store $10^{21} \ll M$ bits, and are operating at no more than $10^{23} \ll V$ ops.

If the evolution of the universe is equivalent to a finite algorithmic procedure, then it is clearly subject to the limitations of a Turing machine, even though it is much more powerful and faster than any conventional computer that can be created. In particular, the finitude of μ means that all possible quantum programs that correspond to physical reality, including $qh(p, i)$ and $r(n)$, can be enumerated at that digital precision. The contradiction that arose in Eq. (1) can no longer be avoided, and we recover the Church-Turing thesis. Similarly, according to the computational resolution principle, a superposition of more than 2^μ states cannot be coherently maintained without interruptions to its unitary evolution. In practice this means that Diophantine equations with possible solutions larger than $2^{10^{23}}$ are effectively uncomputable using U_D in Eq. (3). Suppose all the degrees of freedom in the universe were available for storing information: this can be estimated to be about 10^{120} bits, including gravitational degrees of freedom [16]. Even if we grant $\mu = 10^{120}$ so that coherent evolution of the universe as a whole can be computationally supported, CMQM implies that the number of T_x 's in a finite Turing field equivalent to the quantum algorithm cannot exceed $2^{10^{120}}$; in an arbitrary basis, the number of elements in U_D in Eq. (3) cannot exceed $2^{10^{120}} \times 2^{10^{120}}$. This seems quite unlikely even as the system is 'rotated' over vast tracts of states, corresponding to various potential solutions to $D(x)$. Accordingly, the possible largest solutions to a non-recursive function (such as the solution to an arbitrary Diophantine equation) that can be explored are bounded above by $2^{10^{120}}$. One might say that there is not enough room in the resolution limited Hilbert space $\mathcal{H}_\mu$ of any quantum computer to explore all of the solution space, which is $\mathbb{N}^n$.

The point can be further clarified in taking a spin $\frac{1}{2}$ system. Consider

$$\Omega \equiv \sum_{p \text{ halts}} 2^{-|p|}, \quad (5)$$

Chaitin's constant, which is the probability that an arbitrary program will halt, where $|p|$ is the size (in bits) of program p [17]. Knowing the binary expansion of Ω is equivalent to solving the halting problem for all p . If the universe, and thence the Hilbert space that describes it, are infinite, one might consider an effective method of designing the evolution $U_C \equiv \exp(-i\Omega\sigma_x)$. Applying the dynamics U_C on a system prepared in the $|\uparrow\rangle_z$ state (spin up in the z direction) results in the state:

$$\cos(\Omega)|\uparrow\rangle_z + \sin(\Omega)|\downarrow\rangle_z. \quad (6)$$

By repeatedly performing this procedure and measuring σ_z , we may determine $\cos\Omega$ and thus Ω to any desired accuracy, with arbitrarily high confidence. According to the computational model, however, $\cos\Omega$ can never be known with precision greater than μ . Although μ can be arbitrarily large, and thus in principle Ω calculated in principle to arbitrary precision, in any given instance of the universe, μ is finite and thus Ω can never truly be computed.

This work has discussed whether the observables and dynamics permitted by quantum mechanics permit quantum computation to transcend the Turing barrier that bounds computable functions. If they do, they would in principle contradict the Church-Turing thesis. Using concepts from computer science and in the framework of CMQM, we resolve this conflict by pointing out that the measurement problem implies that a quantum computer corresponds to a finite Turing field. This viewpoint, which is based on a realistic interpretation of the state vector as a not entirely accessible object that resides and evolves in an abstract space, is referred to as 'informational realism'. It is perhaps the simplest and most direct interpretation of the basic mathematical formalism. Its physical content shows up only when the large but finite upper bound it imposes on the dimension of coherently evolving systems is reached.

* Electronic address: srik@rri.res.in

- [1] M. A. Nielsen, Phys. Rev. Lett. **79** 2195, (1997).
- [2] P. Shor, SIAM Journal of Computing **26**, 1484 (1997); L. K. Grover, Phys. Rev. Lett. **79**, 325 (1997).
- [3] A. Turing, Proc. Lond. Math. Soc. (ser 2.) **42**, 230 (1937); (a correction) **45**, 161 (1937).
- [4] R. Penrose, *The Emperor's New Mind* (Oxford University Press, 1989); *Shadows of the Mind* (Vintage, 1995).
- [5] B. J. Copeland, *The Church-Turing Thesis*, The Stanford Encyclopedia of Philosophy (Fall 2002 Edition), Edward N. Zalta (ed.), URL = <<http://plato.stanford.edu/archives/fall12002/entries/church-turing/>>

- [6] D. R. Hofstadter, *Gödel, Escher, Bach: An Eternal Golden Braid* (Basic Books, New York, 1979).
- [7] K. Svozil, in *Unconventional Models of Computation*, eds. Cristian S. Calude, J. Casti and MJ Dineen (Springer-Verlag, Singapore, 1998); eprint quant-ph/9710052.
- [8] R. Srikanth, *Quantum Information Processing* **2**, 153 (2003).
- [9] According to a theorem due to Legendre, all natural numbers can be expressed as the sum of four squares. Eg., $7 = 2^2 + 3 \times 1^2$.
- [10] K. Gödel, *Monatschrifte für Mathematik und Physik* **38**, 173 (1931).
- [11] E. Bernstein and U. Vazirani, *Quantum Complexity Theory* SIAM J. Comput. **26**, 1411 (1997).
- [12] T. D. Kieu, *Intl. J. Theor. Phys.* **42** 1461 (2003); *Contemporary Physics* **44**, 51 (2003).
- [13] Y. V. Matiyasevich, *Hilbert's Tenth Problem* (MIT Press, 1993).
- [14] C. S. Calude and B. Pavlov, *Quantum Information Processing* **1**, 107 (2001); eprint quant-ph/0112087.
- [15] G. Lindblad, *Commun. Math. Phys.* **48**, 119 (1976).
- [16] S. Lloyd, *Phys. Rev. Lett.* **88** (2002) 237901.
- [17] G. Chaitin, *Algorithmic Information Theory* (Cambridge 1987); E. W. Weisstein, MathWorld (Wolfram Web Resource): <http://mathworld.wolfram.com/ChaitinsConstant.html>